



Specifications for SRM Model 1212:

Overall Length (A) 28 ¼" (with butt pad)
Overall Height (B) 7 ½" (w/o sights)
Length of Pull (C) 13 ¼" (with butt pad)
Front Rail (D) - ¼" (Δ receiver rail)
Barrel Length 13" (w/ Breacher 15 ½")
Muzzle Thread Pitch 7/8 - 24
Choke Fixed cylinder bore
Weight 7.0 Lbs (w/ magazine, empty)
Weight (Loaded) 8.0 Lbs (approx, w/12 rds)
Breach Weight 5.6 oz
Chamber 12ga, 2 ¾" or 3", fluted
Capacity 12+1
Operating Principle Semi-automatic,
roller-delayed blowback
Trigger Pull 6 ¼ lbs (average)
Colors Black
Magazine Release Center front, ambidextrous
Magazine Index Levers ... Right & left side, ambidextrous

Specifications for SRM Model 1208:

Overall Length (A) 25 ¼" (with butt pad)
Overall Height (B) 7 ½" (w/o sights)
Length of Pull (C) 13 ¼" (with butt pad)
Front Rail (D) - ¼" (Δ receiver rail)
Barrel Length 10" (w/ Breacher 12 ½")
Muzzle Thread Pitch 7/8 - 24
Choke Fixed cylinder bore
Weight 6 ¾ Lbs (w/ magazine, empty)
Weight (Loaded) 7 ½ Lbs (approx, w/8 rds)
Breach Weight 5.6 oz
Chamber 12ga, 2 ¾" or 3", fluted
Capacity 8+1
Operating Principle Semi-automatic,
roller-delayed blowback
Trigger Pull 6 ¼ lbs (average)
Colors Black
Magazine Release Center front, ambidextrous
Magazine Index Levers Right & left side, ambidextrous



SRM 1212 Semi-Auto Shotgun, Black	SRM1212STB
SRM 1212 Semi-Auto Shotgun, FDE	SRM1212STS
SRM 1208 Semi-Auto Shotgun, Black	SRM1208STB
SRM 1208 Semi-Auto Shotgun, FDE	SRM1208STS
Spare 12 Rd Magazine, Black	SRM1212MSB
Spare 12 Rd Magazine, FDE	SRM1212MSS
Spare 8 Rd Magazine, Black	SRM1208MSB
Spare 8 Rd Magazine, FDE	SRM1208MSS